

TABLE 1: General Characteristics

Catalogue Number		International Reference	Block Filtering Surface [cm ²]	Nominal Volume [cm ³]	Connections				TS [°C]		PS [bar]	Risk Category according to PED	
High water capacity core (1)					SAE Flare	ODS		ODM		min.			max.
Threaded Connections	Solder Connections					∅ [in.]	∅ [mm]	∅ [in.]	∅ [mm]				
4303/2	-	032	47	50	1/4"	-	-	-	-	-40	+80	45 (3)	Art. 3.3
4303/2F (2)	-	-			1/4"	-	-	-	-				
-	4303/2S	032S			-	1/4"	-	3/8"	-				
4303/3	-	033			3/8"	-	-	-	-				
4305/2	-	052	70	80	1/4"	-	-	-	-				
4305/2F (2)	-	-			1/4"	-	-	-	-				
-	4305/2S	052S			-	1/4"	-	3/8"	-				
4305/3	-	053			3/8"	-	-	-	-				
-	4305/3S	053S			-	3/8"	-	1/2"	-				
-	4305/M10S	-			-	-	10	-	12				
4308/2	-	082	103	130	1/4"	-	-	-	-				
4308/2F (2)	-	-			1/4"	-	-	-	-				
-	4308/2S	082S			-	1/4"	-	3/8"	-				
4308/3	-	083			3/8"	-	-	-	-				
4308/3F (2)	-	-			3/8"	-	-	-	-				
-	4308/3S	083S			-	3/8"	-	1/2"	-				
-	4308/M10S	-			-	-	10	-	12				
-	4308/M12S	-			-	-	12	-	14				
4308/4	-	084			1/2"	-	-	-	-				
-	4308/4S	084S			-	1/2"	-	5/8"	16				
4316/2	-	162	155	250	1/4"	-	-	-	-				
4316/3	-	163			3/8"	-	-	-	-				
4316/3F (2)	-	-			3/8"	-	-	-	-				
-	4316/3S	163S			-	3/8"	-	1/2"	-				
-	4316/M10S	-			-	-	10	-	12				
-	4316/M12S	-			-	-	12	-	14				
4316/4	-	164			1/2"	-	-	-	-				
-	4316/4S	164S			-	1/2"	-	5/8"	16				
4316/5	-	165			5/8"	-	-	-	-				
-	4316/5S	165S			-	5/8"	16	3/4"	-				
4330/3	-	303	310	500	3/8"	-	-	-	-				
-	4330/3S	303S			-	3/8"	-	1/2"	-				
4330/4	-	304			1/2"	-	-	-	-				
-	4330/4S	304S			-	1/2"	-	5/8"	16				
4330/5	-	305			5/8"	-	-	-	-				
-	4330/5S	305S			-	5/8"	16	3/4"	-				
4332/4	-	304	255	500	1/2"	-	-	-	-				
-	4332/4S	304S			-	1/2"	-	5/8"	16				
4332/5	-	305			5/8"	-	-	-	-				
-	4332/5S	305S			-	5/8"	16	3/4"	-				
4341/5	-	415	330	670	5/8"	-	-	-	-				
-	4341/5S	415S			-	5/8"	16	3/4"	-				
4341/6	-	416			3/4"	-	-	-	-				
-	4341/6S	416S			-	3/4"	-	7/8"	-				
-	4341/7S	417S			-	7/8"	-	1.1/8"	-				
-	4375/4S	754S			-	1/2"	-	5/8"	16				
-	4375/5S	755S	660	1340	-	5/8"	16	3/4"	-				
-	4375/6S	756S			-	3/4"	-	7/8"	-				
-	4375/7S	757S			-	7/8"	-	1.1/8"	-				
-	4375/9S	759S			-	1.1/8"	-	1.3/8"	35				

(1) 100% molecular sieves; (2) Male-female connections (Inlet female)

(3) PS = 400 psig in compliance with the UL approval