

LIQUID INDICATORS & MOISTURE-LIQUID INDICATORS

TABLE 2: General Characteristics

Catalogue Number		Connections									TS [°C]		PS [bar]	Risk Category according to PED
Liquid Indicators	Moisture Liquid Indicators	Type	SAE Flare	ODS		ODM		for pipe			min.	max.		
				Ø [in.]	Ø [mm]	Ø [in.]	Ø [mm]	Ø [in.]	Ø [mm]	W Foro [mm]				
3610/22	3710/22	male	1/4"	-	-	-	-							
3610/33	3710/33		3/8"	-	-	-	-							
3610/44	3710/44		1/2"	-	-	-	-							
3610/55	3710/55		5/8"	-	-	-	-							
3610/66	3710/66		3/4"	-	-	-	-							
3620/M12	3720/M12	soldering	-	-	12	-	-							
3620/5	3720/5		-	5/8"	16	-	-							
3620/M18	3720/M18		-	-	18	-	-							
3620/M22	3720/M22		-	-	22	-	-							
3640/2	3740/2		-	1/4"	-	-	-							
3640/3	3740/3		-	3/8"	-	-	-							
3640/M10	3740/M10		-	-	10	-	-							
3640/M12	3740/M12		-	-	12	-	-							
3640/4	3740/4		-	1/2"	-	-	-							
3640/5	3740/5		-	5/8"	16	-	-							
3640/M18	3740/M18		-	-	18	-	-		-	-				
3640/6	3740/6		-	3/4"	-	-	-							
3640/7	3740/7		-	7/8"	22	-	-							
3640/9	3740/9		-	1.1/8"	-	-	-					-30	+110	
3650/22	3750/22		male	1/4"	-	-	-	-						
3650/33	3750/33	3/8"		-	-	-	-							
3650/44	3750/44	1/2"		-	-	-	-							
3650/55	3750/55	5/8"		-	-	-	-							
3650/66	3750/66	3/4"		-	-	-	-							
-	3770/M28	soldering	-	-	-	-	28							
-	3770/11		-	-	-	1.3/8"	35							
-	3770/13		-	-	-	1.5/8"	-							
-	3770/M42		-	-	-	-	42							
-	3771/11		-	1.3/8"	35	-	-							
-	3771/M42		-	-	42	-	-							
-	3771/17		-	2.1/8"	-	-	-							
-	3780/5	saddle type	-	-	-	-	-	5/8"	16					
-	3780/M18		-	-	-	-	-	-	-	18				
-	3780/7		-	-	-	-	-	-	7/8"	22				
-	3780/9		-	-	-	-	-	-	1.1/8"	28				
-	3780/11		-	-	-	-	-	-	1.3/8"	35				
-	3781/M28	level glass	-	-	-	-	-	-	-	28				

Art. 3.3

45

I

Art. 3.3

I

35

Excluded