

TABLE 1: General Characteristics																	
Catalogue Number	Solder Connections				Couple of solder connections IN / OUT			Oil connection [SAE Flare]	Oil addition [kg]	Max. differential pressure [bar]	TS [°C]		PS [bar]	Risk Category according to PED			
	ODS		ODM		Catalogue Number	ODS (1)					min.	max.					
	Ø [in.]	Ø [mm]	Ø [in.]	Ø [mm]		Ø [in.]	Ø [mm]										
5540/4	1/2"	–	5/8"	16	–	–	–	1/4"	0,4 / 0,5	21	– 10	+ 130	32	I			
5540/5	5/8"	16	3/4"	–													
5540/7	7/8"	–	1"	–													
5540/9	1.1/8"	–	1.3/8"	35													
5540/11	1.3/8"	35	1.5/8"	–													
5540/13	1.5/8"	–	–	–													
5540/M42	–	42	–	–													
5540/17	2.1/8"	54	–	–	5590/5	5/8"	16	1/4"	0,4 / 0,5	21	– 10	+ 130	32	II			
5520/C	–	–	–	–													
	–	–	–	–											5590/7	7/8"	–
5520/D	–	–	–	–											5590/9	1.1/8"	–
	–	–	–	–											5590/11	1.3/8"	35
	–	–	–	–											5590/13	1.5/8"	–
5520/E	–	–	–	–											5590/M42	–	42

(1) The dimensions of the separator's connections must agree with the discharge diameter of the compressor